



- COCL= Center of opening from cover left side
- COW = Clear opening width
*Recom. $(SBL-2xLAP-100)/2$
 Min. 900, max. $(SBL-2xLAP-G)/2$*
- CL = Cover length incl 2x30 mm end plates
*Recom. $(2xCOW) + (2xLAP) + 100 + (2X30)$
 Min. $(2xCOW) + (2xLAP) + 60$*
- DH = Door leaf height
- SBL = Support beam length
*Recom. $(2xCOW) + (2xLAP) + 100$
 Min. $(2xCOW) + (2xLAP)$, Max. 6100*
- LAP = Overlapping
- G= Space between closed door leaves
- DW= Door width (If door adaptor state DW)
- K= Clear opening width, fixed screens

State when ordering

- COCL=.....mm
- COW=.....mm
- Cover
- CL=.....mm
- SBL=.....mm
- LAP=.....mm
- If not stated LAP = 20*
- G=.....mm
- If not stated G = 0*
- DW=.....mm

Surface treatment

- Silver anodized
- Special anodized.....
- RAL.....
- Special powder coating.....
-

Customer: _____

Door id: _____

Project No: _____

Besam ref: _____

Date: _____

Sign: _____

Sliding door operator
UniSlide - 2

Article No. 500337

F
833081