



- COCL= Center of opening from cover left side
- COW = Clear opening width
Recom. (SBL-2xLAP-100)/2
Min. 900, max. (SBL-2xLAP-G)/2
- CL = Cover length incl 2x30 mm end plates
Recom. (2xCOW) + (2xLAP) + 100 + (2x30)
Min. (2xCOW) + (2xLAP) + 60
- DH = Door leaf height
- SBL = Support beam length
Recom. (2xCOW) + (2xLAP) + 100
Min. (2xCOW) + (2xLAP), Max. 6100
- LAP = Overlapping
- G= Space between door leaf and jamb
- DW= Door width (If door adaptor state DW)
- K= Clear opening width, fixed screens

State when ordering
 COCL=.....mm
 COW=.....mm
 Cover
 CL=.....mm
 SBL=.....mm
 LAP=.....mm
If not stated LAP = 20
 G=.....mm
If not stated G = 0
 DW=.....mm

Surface treatment
 Silver anodized
 Special anodized.....
 RAL.....
 Special powder coating

Customer: _____
 Door id: _____
 Project No: _____

Besam ref: _____
 Date: _____
 Sign: _____

Sliding door operator
UniSlide - 1 R/L (L shown)

Article No. 500335

besam

F **833082**